



# Specification

Mode: ZBT-WE826-T2

Description: Wi-Fi Router

Version: V1.0

Version	Date	History versions	Author
V1.0	2015-5-14	First Version	Haibin Tang

Contact Person

Ms. Irene

Job Title : Sales Manager

Business Phone : +86 15818538755

WhatsApp : +86 13048874535 (Anna Lee)

Skype : sales04@zbt-china.com (Anna Lee)

WeChat : irenelz116888

Email :sales04@zbt-china.com (Anna Lee)

Website:www.zbtlink.com




## Picture

### Contact Person

Ms. Irene

Job Title : Sales Manager

Business Phone : +86 15818538755

WhatsApp : +86 13048874535 (Anna Lee)

Skype : sales04@zbt-china.com (Anna Lee)

WeChat : irenelzl16888

Email :sales04@zbt-china.com (Anna Lee)

Website:www.zbtlink.com



Contact Person

Ms. Irene

Job Title : Sales Manager

Business Phone : +86 15818538755

WhatsApp : +86 13048874535 (Anna Lee)

Skype : sales04@zbt-china.com (Anna Lee)

WeChat : irenelz116888

Email :sales04@zbt-china.com (Anna Lee)

Website:www.zbtlink.com



Contact Person

Ms. Irene

Job Title : Sales Manager

Business Phone : +86 15818538755


WhatsApp : +86 13048874535 (Anna Lee)

Skype : sales04@zbt-china.com (Anna Lee)

WeChat : irenelz116888

Email :sales04@zbt-china.com (Anna Lee)

Website:www.zbtlink.com



## 1. Simply Description:

Contact Person

Ms. Irene

Job Title : Sales Manager

Business Phone : +86 15818538755

WhatsApp : +86 13048874535 (Anna Lee)

Skype : sales04@zbt-china.com (Anna Lee)

WeChat : irenelz116888

Email :sales04@zbt-china.com (Anna Lee)

Website:www.zbtlink.com



The WE826 uses the latest wireless solution, performs better and more function. Stable wireless performance, more functions , 2.4G 300Mbps, Also support 3G,4G (3G、4G PCIE mode is necessary), it could also dial-up via the USB port (should mount the 3G,4G network card) . Provide 1 USB2.0 interface, 1 Micro slot.

## 2. Product Feature:

- ◆ Support 802.11N/802.11G/802.11B network protocol, the max transmission rate could be 2.4G 300Mbps

- ◆ Support 802.113/802.11U protocol, 5\* 10/100M bps Auto MDI/MDIX

- ◆ 1 USB 2.0 data interface

- ◆ 1 Micro SD Card Slot

Contact Person

Ms. Irene

Job Title : Sales Manager

Business Phone : +86 15818538755

WhatsApp : +86 13048874535 (Anna Lee)

Skype : sales04@zbt-china.com (Anna Lee)

WeChat : irenelz116888

Email :sales04@zbt-china.com (Anna Lee)

Website:www.zbtlink.com



- ◆ Support 3G/4G
- ◆ Many kinds of encryption to protect your data transmission;

### 3. Specification:

Hardware	
Main Chipset	MT7620A
RAM	DDR2 128MB (MAX DDR2 256MB)
SPI FLASH	16MB (MAX 32MB)
Protocol	IEEE 802.11n、IEEE 802.11g.IEEE 802.11b.IEEE 802.3u
RT Power	802.11b 18dBm±2dBm; 802.11g 15dBm±2dBm; 802.11n 15dBm±2dBm;
Reception Sensitivity	802.11b: -83dBm@10% PER 802.11g: -74dBm@10% PER 802.11n: -68dBm@10% PER
Work Channel	2.4GHz choose : 1-13
Wireless Rate	Max 300Mbps
Work Frequency	2.4GHz
Antenna	2*detachable 5dBi antenna
Interface	1*PCI-E slot 1*SIM card slot

#### Contact Person

Ms. Irene

Job Title : Sales Manager

Business Phone : +86 15818538755

WhatsApp : +86 13048874535 (Anna Lee)

Skype : sales04@zbt-china.com (Anna Lee)

WeChat : irenelz116888

Email :sales04@zbt-china.com (Anna Lee)

Website:www.zbtlink.com



	1*USB 2.0 port 1*Micro SD card slot 1*10/100M WAN port (Auto MDI/MDIX) 4*10/100M LAN port (Auto MDI/MDIX)
LED	Power,PCIE mode ,2.4G,WAN,LAN1,LAN2,LAN3,LAN4
Button	Reset/WPS
Max Power consumption	< 12W
Dimension (L*W*H)	<b>141*85*26MM</b>
<b>Software</b>	
WAN Type	PPPoE.Dynamic IP. Static IP
Work Mode	AP; Router;
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Firewall Security	Dos, SPI Firewall IP Address Filter/MAC Address Filter/ Domain Filter IP and MAC Address Binding
DDNS	Support
VPN Pass-Through	PPTP, L2TP, IPsec (ESP Head)
Band Ctrl	Support
Static Router	Support
System Log	Support
Other	Mac clone

### Contact Person

Ms. Irene

Job Title : Sales Manager

Business Phone : +86 15818538755

WhatsApp : +86 13048874535 (Anna Lee)

Skype : sales04@zbt-china.com (Anna Lee)

WeChat : irenelz116888

Email :sales04@zbt-china.com (Anna Lee)

Website:www.zbtlink.com





Function	NTP Synchronize Web firmware upgrade
<b>Others</b>	
Work Environments	Operating Temperature: 0°C ~ 40°C; Storage Temperature: -40°C ~ 70°C; Operating Humidity: 10%~90% non-condensing Storage Humidity: 10%~90% non-condensing
Adapter	12V 1A
Authentication	<b>CE, FCC, RoHs</b>
Other accessories	Power adapter

## Contact Person

Ms. Irene

Job Title : Sales Manager

Business Phone : +86 15818538755

WhatsApp : +86 13048874535 (Anna Lee)

Skype : sales04@zbt-china.com (Anna Lee)

WeChat : irenelz116888

Email :sales04@zbt-china.com (Anna Lee)

Website:www.zbtlink.com